

SAFETY DATA SHEET

according to Commission Regulation (EU) 2020/878 as amended

Katalizator (do zalew silikonowych 011,019,021,029)

Creation date	24th May 2022	Version	9.0
Revision date	14th January 2025		

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- 1.1. Product identifier**
 Substance / mixture: Katalizator (do zalew silikonowych 011,019,021,029)
 UFI: SN40-907P-G00T-J2QS
- 1.2. Relevant identified uses of the substance or mixture and uses advised against**
Mixture's intended use
 Catalyst.
Main intended use
 PC-TEC-27 Products for the polymerisation of resins and foams (includes curing agents, hardeners, cross-linkers)
Mixture uses advised against
 The product should not be used in ways other than those referred in Section 1.
- 1.3. Details of the supplier of the safety data sheet**
Supplier
 Name or trade name: AG TermoPasty Grzegorz Gąsowski
 Address: Kolejowa 33 E, Sokoły, 18-218
 Poland
 Identification number (CRN): 200133730
 VAT Reg No: PL9661767714
 Phone: +48 86 274 13 42
 E-mail: msds@termopasty.pl
 Web address: www.termopasty.com
- Competent person responsible for the safety data sheet**
 Name: AG TermoPasty Grzegorz Gąsowski
 E-mail: msds@termopasty.pl
- 1.4. Emergency telephone number**
 European emergency number: 112

SECTION 2: Hazards identification

- 2.1. Classification of the substance or mixture**
Classification of the mixture in accordance with Regulation (EC) No 1272/2008
 The mixture is classified as dangerous.
- Flam. Liq. 3, H226
 Eye Irrit. 2, H319
 Acute Tox. 4, H332
 STOT SE 3, H335
 Repr. 1B, H360D
 STOT RE 1, H372 (immune system)
- Most serious adverse physico-chemical effects**
 Flammable liquid and vapour.
- Most serious adverse effects on human health and the environment**
 Causes serious eye irritation. Harmful if inhaled. May cause respiratory irritation. May cause damage to organs.
- 2.2. Label elements**
Hazard pictogram
- 


- Signal word**
 Danger
- Hazardous substances**
 tetraethyl silicate
 dioctyltin dilaurate

SAFETY DATA SHEET

according to Commission Regulation (EU) 2020/878 as amended

Katalizator (do zalew silikonowych 011,019,021,029)

Creation date	24th May 2022	Version	9.0
Revision date	14th January 2025		

Hazard statements

H226	Flammable liquid and vapour.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H360D	May damage the unborn child.
H372	Causes damage to the immune system through prolonged or repeated exposure.

Precautionary statements

P202	Do not handle until all safety precautions have been read and understood.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P260	Do not breathe mist/vapours/spray.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P308+P313	IF exposed or concerned: Get medical advice/attention.

Label elements for packages not exceeding 125 ml

Hazard pictogram



Signal word

Danger

Hazardous substances

tetraethyl silicate
dioctyltin dilaurate

Hazard statements

H360D	May damage the unborn child.
H372	Causes damage to the immune system through prolonged or repeated exposure.

Precautionary statements

P202	Do not handle until all safety precautions have been read and understood.
P260	Do not breathe mist/vapours/spray.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P308+P313	IF exposed or concerned: Get medical advice/attention.

2.3. Other hazards

The mixture does not contain substances with endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605. Mixture does not contain any substance meet the criteria for PBT or vPvB in accordance with Annex XIII of Regulation (EC) No. 1907/2006 (REACH) as amended. Does not contain any PMT or vPvM components.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Mixture contains these hazardous substances and substances with the highest permissible concentration in the working environment

Identification numbers	Substance name	Content in % weight	Classification according to Regulation (EC) No 1272/2008	Note
Index: 014-005-00-0 CAS: 78-10-4 EC: 201-083-8 Registration number: 01-2119496195-28-XXXX	tetraethyl silicate	>25	Flam. Liq. 3, H226 Eye Irrit. 2, H319 Acute Tox. 4, H332 STOT SE 3, H335	1

SAFETY DATA SHEET

according to Commission Regulation (EU) 2020/878 as amended

Katalizator (do zalew silikonowych 011,019,021,029)

Creation date	24th May 2022	Version	9.0
Revision date	14th January 2025		

Identification numbers	Substance name	Content in % weight	Classification according to Regulation (EC) No 1272/2008	Note
Index: 050-031-00-9 CAS: 3648-18-8 EC: 222-883-3 Registration number: 01-2119979527-19-XXXX	dioctyltin dilaurate	15	Repr. 1B, H360D STOT RE 1, H372 (immune system)	2, 3

Notes

- 1 A substance for which exposure limits are set.
- 2 Substance of very high concern - SVHC.
- 3 The use of the substance is restricted by Annex XVII of REACH Regulation

Full text of all classifications and hazard statements is given in the section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

Take care of your own safety. If any health problems are manifested or if in doubt, inform a doctor and show him information from this safety data sheet. If unconscious, put the person in the stabilized (recovery) position on his side with his head slightly bent backwards and make sure that airways are free; never induce vomiting. If the person vomits by himself, make sure that the vomit is not inhaled. In life threatening conditions first of all provide resuscitation of the affected person and ensure medical assistance. Respiratory arrest - provide artificial respiration immediately. Cardiac arrest - provide indirect cardiac massage immediately.

If inhaled

Terminate the exposure immediately; move the affected person to fresh air. Protect the person against growing cold. Provide medical treatment if irritation, dyspnoea or other symptoms persist.

If on skin

Remove contaminated clothes. Wash the affected area with plenty of water, lukewarm if possible. Soap, soap solution or shampoo should be used if there is no skin injury. Provide medical treatment if skin irritation persists. Rinse skin with water or shower.

If in eyes

Rinse eyes immediately with a flow of running water, open the eyelids (also using force if needed); remove contact lenses immediately if worn by the affected person. Rinsing should continue at least for 10 minutes. Provide medical treatment, specialized if possible.

If swallowed

Provide medical treatment.

4.2. Most important symptoms and effects, both acute and delayed

If inhaled

Cough, headache. May cause respiratory irritation.

If on skin

Not expected.

If in eyes

Causes serious eye irritation.

If swallowed

Irritation, nausea.

4.3. Indication of any immediate medical attention and special treatment needed

Symptomatic treatment.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Alcohol-resistant foam, carbon dioxide, powder, water spray jet, water mist.

Unsuitable extinguishing media

Water - full jet.

SAFETY DATA SHEET

according to Commission Regulation (EU) 2020/878 as amended

Katalizator (do zalew silikonowych 011,019,021,029)

Creation date 24th May 2022
Revision date 14th January 2025 Version 9.0

5.2. Special hazards arising from the substance or mixture

In the event of fire, carbon monoxide, carbon dioxide and other toxic gases may arise. Inhalation of hazardous degradation (pyrolysis) products may cause serious health damage.

5.3. Advice for firefighters

Self-Contained Breathing Apparatus (SCBA) with a chemical protection suit only where personal (close) contact is likely. Use a self-contained breathing apparatus and full-body protective clothing. Closed containers with the product near the fire should be cooled with water. Do not allow run-off of contaminated fire extinguishing material to enter drains or surface and ground water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Provide sufficient ventilation. Flammable liquid and vapour. Remove all ignition sources. Use personal protective equipment for work. Follow the instructions in the Sections 7 and 8. Do not inhale mist/vapours/spray. Prevent contact with skin and eyes.

6.2. Environmental precautions

Prevent contamination of the soil and entering surface or ground water.

6.3. Methods and material for containment and cleaning up

Spilled product should be covered with suitable (non-flammable) absorbing material (sand, diatomaceous earth, earth and other suitable absorption materials); to be contained in well closed containers and removed as per the Section 13. In the event of leakage of the substantial amount of the product, inform fire brigade and other competent bodies. After removal of the product, wash the contaminated site with plenty of water. Do not use solvents.

6.4. Reference to other sections

See the Section 7, 8 and 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Prevent formation of gases and vapours in flammable or explosive concentrations and concentrations exceeding the occupational exposure limits. The product should be used only in the areas where it is not in contact with open fire and other ignition sources. Use non-sparking tools. Use of antistatic clothes and footwear is recommended. Do not inhale mist/vapours/spray. Prevent contact with skin and eyes. No smoking. Do not eat, drink or smoke when using this product. Wash hands and exposed parts of the body thoroughly after handling. Use only outdoors or in a well-ventilated area. Use personal protective equipment as per Section 8. Observe valid legal regulations on safety and health protection. Ground and bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Take action to prevent static discharges.

7.2. Conditions for safe storage, including any incompatibilities

Store in tightly closed containers in cold, dry and well ventilated areas designated for this purpose. Do not expose to sunlight. Store locked up. Keep container tightly closed. Keep cool.

Content	Packaging type	Material of package
100 g	box	FE
10 g	syringe	PET

The specific requirements or rules relating to the substance/mixture

Solvent vapours are heavier than air and accumulate especially near the floor where they may form an explosive mixture with the air.

7.3. Specific end use(s)

not available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

The mixture contains substances for which occupational exposure limits are set.

European Union

Commission Directive (EU) 2017/164

Substance name (component)	Type	Value
tetraethyl silicate (CAS: 78-10-4)	OEL 8 hours	44 mg/m ³
	OEL 8 hours	5 ppm

SAFETY DATA SHEET

according to Commission Regulation (EU) 2020/878 as amended

Katalizator (do zalew silikonowych 011,019,021,029)

Creation date	24th May 2022	Version	9.0
Revision date	14th January 2025		

DNEL

tetraethyl silicate			
Workers / consumers	Route of exposure	Value	Effect
Workers	Inhalation	85 mg/m ³	Acute effects systemic
Workers	Inhalation	85 mg/m ³	Acute effects systemic
Workers	Inhalation	85 mg/m ³	Chronic effects systemic
Workers	Dermal	12.1 mg/kg/24h	Acute effects systemic
Workers	Dermal	12.1 mg/kg/24h	Chronic effects systemic
Consumers	Inhalation	25 mg/m ³	Chronic effects systemic
Consumers	Inhalation	25 mg/m ³	Chronic effects local
Consumers	Dermal	8.4 mg/m ³ /24h	Chronic effects systemic

PNEC

tetraethyl silicate	
Route of exposure	Value
Drinking water	0.192 mg/l
Marine water	0.0192 mg/l
Freshwater sediment	0.18 mg/kg
Sea sediments	0.018 mg/kg
Soil (agricultural)	0.05 mg/kg
Microorganisms in sewage treatment	400 mg/l
Water (intermittent release)	10 mg/l

8.2. Exposure controls

Follow the usual measures intended for health protection at work and especially for good ventilation. This can be achieved only by local suction or efficient general ventilation. If exposure limits cannot be observed in this mode, suitable protection of airways must be used. Do not eat, drink and smoke during work. Wash your hands thoroughly with water and soap after work and before breaks for a meal and rest.

Eye/face protection

Protective goggles.

Skin protection

Hand protection: Protective gloves resistant to the product. When choosing appropriate thickness, material and permeability of the gloves, observe recommendations of their particular manufacturer. Contaminated skin should be washed thoroughly.

Respiratory protection

Halfmask with a filter against organic vapours or a self-contained breathing apparatus as appropriate if exposure limit values of substances are exceeded or in a poorly ventilated environment.

Thermal hazard

Data not available.

Environmental exposure controls

Observe usual measures for protection of the environment, see Section 6.2.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	liquid
Colour	yellow
Odour	characteristic
Melting point/freezing point	data not available
Boiling point or initial boiling point and boiling range	90 °C
Flammability	data not available
Lower and upper explosion limit	

SAFETY DATA SHEET

according to Commission Regulation (EU) 2020/878 as amended

Katalizator (do zalew silikonowych 011,019,021,029)

Creation date	24th May 2022	Version	9.0
Revision date	14th January 2025		

bottom	1.3 %
upper	23 %
Flash point	50 °C
Auto-ignition temperature	data not available
Decomposition temperature	data not available
pH	6 (undiluted)
Kinematic viscosity	data not available
Viscosity	0.53 cP
Solubility in water	insoluble
Partition coefficient n-octanol/water (log value)	data not available
Vapour pressure	2 hPa at 20 °C
Density and/or relative density	
Density	0.939 g/cm ³
Relative vapour density	data not available
Particle characteristics	data not available
Form	liquid

9.2. Other information

Explosive properties	Vapours mixed up with air can be explosive.
----------------------	---

SECTION 10: Stability and reactivity

10.1. Reactivity

not available

10.2. Chemical stability

The product is stable under normal conditions.

10.3. Possibility of hazardous reactions

Unknown.

10.4. Conditions to avoid

The product is stable and no degradation occurs under normal use. Protect against flames, sparks, overheating and against frost.

10.5. Incompatible materials

Protect against strong acids, bases and oxidizing agents.

10.6. Hazardous decomposition products

Not developed under normal uses. Dangerous outcomes such as carbon monoxide and carbon dioxide are formed at high temperature and in fire.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Inhalation of solvent vapors above values exceeding exposure limits for working environment may result in acute inhalation poisoning, depending on the level of concentration and exposure time. No toxicological data is available for the mixture.

Acute toxicity

Harmful if inhaled. May cause damage to organs.

tetraethyl silicate					
Route of exposure	Parameter	Value	Exposure time	Species	Sex
Oral	LD ₅₀	6270 mg/kg		Rat	
Dermal	LD ₅₀	5850 mg/kg		Rabbit	
Inhalation (vapor)	LC ₅₀	5.03 mg/l	4 hours	Rat	
Inhalation	LC ₅₀	1000 ppm	4 hours	Rat	

Skin corrosion/irritation

Based on available data the classification criteria are not met.

SAFETY DATA SHEET

according to Commission Regulation (EU) 2020/878 as amended

Katalizator (do zalew silikonowych 011,019,021,029)

Creation date 24th May 2022
Revision date 14th January 2025 Version 9.0

Serious eye damage/irritation

Causes serious eye irritation.

Respiratory or skin sensitisation

Based on available data the classification criteria are not met.

Germ cell mutagenicity

Based on available data the classification criteria are not met.

Carcinogenicity

Based on available data the classification criteria are not met.

Reproductive toxicity

Based on available data the classification criteria are not met.

Toxicity for specific target organ - single exposure

May cause respiratory irritation. May cause damage to organs.

Toxicity for specific target organ - repeated exposure

Based on available data the classification criteria are not met.

Aspiration hazard

Based on available data the classification criteria are not met.

11.2. Information on other hazards**Endocrine disrupting properties**

Based on the available data, the criteria for classification of the mixture are not met. Does not contain any components that may cause endocrine disruption for humans.

Other information

not available

SECTION 12: Ecological information**12.1. Toxicity**

not available

Acute toxicity

tetraethyl silicate				
Parameter	Value	Exposure time	Species	Environment
EC ₅₀	>844 mg/l	48 hours	Daphnia (Daphnia magna)	
EC ₅₀	>2 mg/l	5 hours	Bacteria (Pseudomonas putida)	

12.2. Persistence and degradability

not available

12.3. Bioaccumulative potential

Data not available.

12.4. Mobility in soil

Data not available.

12.5. Results of PBT and vPvB assessment

Based on the available data, the criteria for classification of the mixture are not met. Does not contain any PBT or vPvB components.

12.6. Endocrine disrupting properties

Based on the available data, the criteria for classification of the mixture are not met. Does not contain any components that may cause endocrine disruption in the environment.

SAFETY DATA SHEET

according to Commission Regulation (EU) 2020/878 as amended

Katalizator (do zalew silikonowych 011,019,021,029)

Creation date	24th May 2022		
Revision date	14th January 2025	Version	9.0

12.7. Other adverse effects

Data not available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Hazard of environmental contamination; dispose of the waste in accordance with the local and/or national regulations. Any unused product and contaminated packaging should be put in labelled containers for waste collection and submitted for disposal to a person authorised for waste removal (a specialized company) that is entitled for such activity. Do not empty unused product in drainage systems. The product must not be disposed of with municipal waste. Empty containers may be used at waste incinerators to produce energy or deposited in a dump with appropriate classification. Perfectly cleaned containers can be submitted for recycling.

Waste management legislation

Directive 2008/98/EC of the European Parliament and of the Council of 19 November 2008 on waste, as amended. Decision 2000/532/EC establishing a list of wastes, as amended.

SECTION 14: Transport information

14.1. UN number or ID number

UN 1993

14.2. UN proper shipping name

FLAMMABLE LIQUID, N.O.S.

14.3. Transport hazard class(es)

3 Flammable liquids

14.4. Packing group

III

14.5. Environmental hazards

not relevant

14.6. Special precautions for user

Reference in the Sections 4 to 8.

14.7. Maritime transport in bulk according to IMO instruments

not relevant

Additional information

Hazard identification No.

30

UN number

1993

Classification code

F1

Safety signs

3



Tunnel restriction code

(D/E)

Marine transport - IMDG

EmS (emergency plan)

F-E, S-E

MFAG

310

SAFETY DATA SHEET

according to Commission Regulation (EU) 2020/878 as amended

Katalizator (do zalew silikonowych 011,019,021,029)

Creation date	24th May 2022		
Revision date	14th January 2025	Version	9.0

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Regulation (EC) No. 1907/2006 of the European Parliament and of the Council of 18th December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing the European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No. 793/93 and Commission Regulation (EC) No. 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC, as amended. REGULATION (EC) No. 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL as amended. Commission Regulation (EU) 2020/878 of 18 June 2020 amending Annex II to Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH).

Restrictions pursuant to Annex XVII of Regulation (EC) No. 1907/2006 (REACH), as amended

dioctyltin dilaurate

Restriction	Conditions of restriction
30	<p>1. Shall not be placed on the market, or used,</p> <ul style="list-style-type: none"> — as substances, — as constituents of other substances, or, — in mixtures, for supply to the general public when the individual concentration in the substance or mixture is equal to or greater than: <ul style="list-style-type: none"> — either the relevant specific concentration limit specified in Part 3 of Annex VI to Regulation (EC) No 1272/2008, or, — the relevant generic concentration limit specified in Part 3 of Annex I of Regulation (EC) No 1272/2008. <p>Without prejudice to the implementation of other Community provisions relating to the classification, packaging and labelling of substances and mixtures, suppliers shall ensure before the placing on the market that the packaging of such substances and mixtures is marked visibly, legibly and indelibly as follows:</p> <p>“Restricted to professional users”.</p> <p>2. By way of derogation, paragraph 1 shall not apply to:</p> <ul style="list-style-type: none"> (a) medicinal or veterinary products as defined by Directive 2001/82/EC and Directive 2001/83/EC; (b) cosmetic products as defined by Directive 76/768/EEC; (c) the following fuels and oil products: <ul style="list-style-type: none"> — motor fuels which are covered by Directive 98/70/EC, — mineral oil products intended for use as fuel in mobile or fixed combustion plants, — fuels sold in closed systems (e.g. liquid gas bottles); (d) artists’ paints covered by Regulation (EC) No 1272/2008; (e) the substances listed in Appendix 11, column 1, for the applications or uses listed in Appendix 11, column 2. Where a date is specified in column 2 of Appendix 11, the derogation shall apply until the said date. (f) devices covered by Regulation (EU) 2017/745.

15.2. Chemical safety assessment

A chemical safety assessment has not been carried out (mixture).

SECTION 16: Other information

A list of standard risk phrases used in the safety data sheet

H226	Flammable liquid and vapour.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H360D	May damage the unborn child.
H372	Causes damage to the immune system through prolonged or repeated exposure.

Guidelines for safe handling used in the safety data sheet

P202	Do not handle until all safety precautions have been read and understood.
P260	Do not breathe mist/vapours/spray.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P308+P313	IF exposed or concerned: Get medical advice/attention.

SAFETY DATA SHEET

according to Commission Regulation (EU) 2020/878 as amended

Katalizator (do zalew silikonowych 011,019,021,029)

Creation date	24th May 2022	Version	9.0
Revision date	14th January 2025		

- | | |
|----------------|--|
| P210 | Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. |
| P303+P361+P353 | IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. |
| P304+P340 | IF INHALED: Remove person to fresh air and keep comfortable for breathing. |

Other important information about human health protection

The product must not be - unless specifically approved by the manufacturer/importer - used for purposes other than as per the Section 1. The user is responsible for adherence to all related health protection regulations.

Key to abbreviations and acronyms used in the safety data sheet

- | | |
|------------------|---|
| Acute Tox. | Acute toxicity |
| ADR | European agreement concerning the international carriage of dangerous goods by road |
| BCF | Bioconcentration Factor |
| CAS | Chemical Abstracts Service |
| CLP | Regulation (EC) No 1272/2008 on classification, labelling and packaging of substance and mixtures |
| EC | Identification code for each substance listed in EINECS |
| EC ₅₀ | Concentration of a substance when it is affected 50 % of the population |
| EINECS | European Inventory of Existing Commercial Chemical Substances |
| EmS | Emergency plan |
| EU | European Union |
| EuPCS | European Product Categorisation System |
| Eye Irrit. | Eye irritation |
| Flam. Liq. | Flammable liquid |
| IATA | International Air Transport Association |
| IBC | International Code For The Construction And Equipment of Ships Carrying Dangerous Chemicals |
| ICAO | International Civil Aviation Organization |
| IMDG | International Maritime Dangerous Goods |
| IMO | International Maritime Organization |
| INCI | International Nomenclature of Cosmetic Ingredients |
| ISO | International Organization for Standardization |
| IUPAC | International Union of Pure and Applied Chemistry |
| LC ₅₀ | Lethal concentration of a substance in which it can be expected death of 50% of the population |
| LD ₅₀ | Lethal dose of a substance in which it can be expected death of 50% of the population |
| log Kow | Octanol-water partition coefficient |
| OEL | Occupational Exposure Limits |
| PBT | Persistent, bioaccumulative and toxic |
| PMT | Persistent, mobile and toxic |
| ppm | Parts per million |
| REACH | Registration, Evaluation, Authorisation and Restriction of Chemicals |
| Repr. | Reproductive toxicity |
| RID | Agreement on the transport of dangerous goods by rail |
| STOT RE | Specific target organ toxicity - repeated exposure |
| STOT SE | Specific target organ toxicity - single exposure |
| UN | Four-figure identification number of the substance or article taken from the UN Model Regulations |
| UVCB | Substances of unknown or variable composition, complex reaction products or biological materials |
| VOC | Volatile organic compounds |
| vPvB | Very persistent and very bioaccumulative |
| vPvM | Very persistent and very mobile |

Training guidelines

Inform the personnel about the recommended ways of use, mandatory protective equipment, first aid and prohibited ways of handling the product.

SAFETY DATA SHEET

according to Commission Regulation (EU) 2020/878 as amended

Katalizator (do zalew silikonowych 011,019,021,029)

Creation date	24th May 2022		
Revision date	14th January 2025	Version	9.0

Recommended restrictions of use

not available

Information about data sources used to compile the Safety Data Sheet

REGULATION (EC) No. 1907/2006 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL (REACH) as amended.
REGULATION (EC) No. 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL as amended. Data from the manufacturer of the substance / mixture, if available - information from registration dossiers.

The changes (which information has been added, deleted or modified)

The version 9.0 replaces the SDS version from Tuesday, 16 January 2024. Changes were made in sections 2, 11, 12, 13 and 16.

More information

Classification procedure - calculation method.

Statement

The safety data sheet provides information aimed at ensuring safety and health protection at work and environmental protection. The provided information corresponds to the current status of knowledge and experience and complies with valid legal regulations. The information should not be understood as guaranteeing the suitability and usability of the product for a particular application.