

KZS-AFDD 3M2p A B16/0.03



Specificatii

Cod ETI	002173814
Descriere	KZS-AFDD 3M2p A B16/0.03
Denumire clasă	Dispozitiv detectare arc (AFDD)
Curent nominal (A)	16A
Tip	A
Curent de defect nominal (A)	0.03A
Caracteristică de întrerupere	B
Număr de poli	2
Capacitatea de rupere (kA)	10kA
Sec iune transversală nominală	1mm ² -25mm ²
Standarde	IEC/EN 61009-1, IEC/EN 62606

[Pagina de produse online](#)


Alta documentatie

[Catalog caracteristici tehnice](#)[Model 3D](#)[2D mușchi](#)[Manual de instructiuni](#)[Declaratie CE](#)[Eplan mușchi](#)



ETIM clasificare internațională

Clasificare	EC000905
Denumire clasă	Earth leakage circuit breaker
Number of poles (total)	2
Number of protected poles	2
Rated voltage	240V
Rated impulse withstand voltage U _{imp}	4kV
Rated current	16A
Rated fault current	0,03A
Leakage current type	A
Current limiting class	3
Rated short-circuit breaking capacity according to EN 61009	10kA
Frequency	50 Hz
Release characteristic	B
Ambient temperature during operating	-25...40°C
Width in number of modular spacings	3
Built-in depth	69mm
Degree of protection (IP)	IP20
Connectable conductor cross section solid-core	1...25mm ²
Connectable conductor cross section multi-wired	1...25mm ²

Caracteristicile energiei de topire



Desen cotat



Simbol/Conexiune

