

ETIMAT 1N 1p+N B10 6kA



Specificatii

Cod ETI	002191102
Descriere	ETIMAT 1N 1p+N B10 6kA
Denumire clasă	Disjunctori miniatural
Curent nominal (A)	10A
Caracteristică de întrerupere	B
Număr de poli	1+N
Capacitatea de rupere (kA)	6kA
Tipul voltajului	AC
Tensiunea nominală de rezistență Uimp (kV)	4kV
Tensiune nominală AC (V)	230V
Frecvență nominală (Hz)	50Hz/60Hz
Secțiune transversală nominală	1mm ² -10mm ²
Standarde	IEC/EN 60898-1
Funcție	MCB

[Pagina de produse online](#)

Alta documentatie

[Catalog caracteristici tehnice](#)[Certificate](#)[Model 3D](#)[2D mușchi](#)[Manual de instrucțiuni](#)[Declaratie CE](#)[Eplan mușchi](#)

ETIM clasificare internationala

Clasificare	EC000042
Denumire clasă	Miniature circuit breaker (MCB)
Release characteristic	B
Number of poles (total)	2
Number of protected poles	1
Rated current	10A
Rated voltage	230V
Rated impulse withstand voltage Uimp	4kV
Rated short-circuit breaking capacity Icn according to EN 60898 at 230 V	6kA
Rated short-circuit breaking capacity Icu according to IEC 60947-2 at 400 V	6kA
Voltage type	AC
Frequency	50...50Hz
Current limiting class	3
Concurrently switching neutral conductor	Da
Width in number of modular spacings	1
Built-in depth	68mm
Degree of protection (IP)	IP20
Connectable conductor cross section multi-wired	1...10mm ²
Connectable conductor cross section solid-core	1...10mm ²

Desen cotat

