

ETIMAT P6 1p C13



Specificatii

Cod ETI	001900029
Descriere	ETIMAT P6 1p C13
Denumire clasă	Disjunctori miniatural
Curent nominal (A)	13A
Caracteristică de întrerupere	C
Număr de poli	1
Capacitatea de rupere (kA)	6kA
Tipul voltajului	AC
Tensiunea nominală de rezistență Uimp (kV)	6kV
Tensiune nominală AC (V)	240V/415V
Frecvență nominală (Hz)	50Hz/60Hz
Secțiune transversală nominală	1mm ² -25mm ²
Standarde	60898-1,60947-2
Funcție	MCB

[Pagina de produse online](#)


Alta documentatie

[Catalog caracteristici tehnice](#)[Model 3D](#)[2D mușchi](#)[Manual de instrucțiuni](#)[Declarație CE](#)[Eplan mușchi](#)


ETIM clasificare internationala

Clasificare	EC000042
Denumire clasă	Miniature circuit breaker (MCB)
Release characteristic	C
Number of poles (total)	1
Number of protected poles	1
Rated current	13A
Rated voltage	240/415V
Rated insulation voltage U_i	500V
Rated impulse withstand voltage U_{imp}	6kV
Rated short-circuit breaking capacity I_{cn} according to EN 60898 at 230 V	6kA
Rated short-circuit breaking capacity I_{cn} according to EN 60898 at 400 V	6kA
Rated short-circuit breaking capacity I_{cu} according to IEC 60947-2 at 230 V	6kA
Rated short-circuit breaking capacity I_{cu} according to IEC 60947-2 at 400 V	6kA
Voltage type	AC
Frequency	50...60Hz
Current limiting class	3
Suitable for flush-mounted installation	Da
Concurrently switching neutral conductor	Da
Over voltage category	3
Pollution degree	2
Additional equipment possible	Da
Width in number of modular spacings	1
Built-in depth	70mm
Degree of protection (IP)	IP20
Ambient temperature during operating	-40...70°C
Connectable conductor cross section multi-wired	1...25mm ²
Connectable conductor cross section solid-core	1...25mm ²

Caracteristicile energiei de topire



Desen cotat



Simbol/Conexiune

1p



1p+n



2p



3p



3p+n

